

**Exploring the Selective Generation of Arsenic Hydrides in Quaternary Ammonium Salt Suspension: A Didactic and Systematic Qualitative Approach Applied to Wastewater Treatment**


**Bruno Elias dos Santos Costa\* <sup>a</sup>, Luciano Alves da Silva <sup>a</sup>, and Nívia Maria Melo Coelho <sup>a</sup>**

<sup>a</sup> Institute of Chemistry, Federal University of Uberlândia (UFU), Av. João Naves de Ávila 2121, CEP 38400-902, Uberlândia, Minas Gerais, Brazil.


\*brunoeliassantos@yahoo.com.br

**Supplementary Material**


## Details of the instrumental apparatus and determination of the optimal conditions of the HG AAS flow system




**Figure S1.** Real illustration of the HG AAS system schematic depicted in Figure 1. (Source: The authors)




**Figure S2.** Effect of the variation in the flow rates of sample and NaBH<sub>4</sub> solutions. The highlighted value represents the selected condition.



**Figure S3.** Effect of the variation of water flow as a carrier. The highlighted value represents the selected condition.




**Figure S4.** Effect of the variation of drainage flow (gas-liquid separator outlet channel). The highlighted value represents the selected condition.



**Figure S5.** Effect of the variation of sample and NaBH<sub>4</sub> injected volumes. The highlighted value represents the selected condition (corresponding to the activation time of valves V1 and

V2 of 5.0 s). The relationship between injected volume and valve activation time is given by the factor of  $41.67 \mu\text{L s}^{-1}$ .



**Figure S6.** Effect of variation in the length of the reaction coil. The highlighted value represents the selected condition.